

Hydraulic connections

Hydraulic connections on the DOP350

Sets of hydraulic hoses for the DOP pump: standard length 20m can be provided.
A set consist of three hydraulic hoses (pressure, return, leak), provided with a quick coupling at each end.
Each hose provided with a male and a female Snap-tite connection.

Pressure	Female	2" 75C32-32RP
Return	Male	2" 75N32-32RP
Leak	Male	1" 75N16-16RP
Working pressure	[bar]	250

Hydraulic connections on the Cutter unit

Sets of hydraulic hoses for the cutter unit: standard length 20m can be provided.
A set consist of three hydraulic hoses (pressure, return, leak), provided with a quick coupling at each end.
Each hose provided with a male and a female Snap-tite connection.

Pressure	Female	1" 75C16-16RP
Return	Male	1" 75N16-16RP
Leak	Male	½" VHN8-8RP
Working pressure	[bar]	250

Hydraulic connections on the Auger unit

Sets of hydraulic hoses for the auger unit: standard length 20m can be provided.
A set consist of five hydraulic hoses (pressure, return, leak, cylinders), provided with a quick coupling at each end.
Each hose provided with a male and a female Snap-tite connection (except the hoses for the cylinders which are provided with a Stucchi connection).

Pressure	Female	Pressure
Return	Male	Return
Leak	Male	Leak
Working pressure	[bar]	Working pressure

AUGER CYLINDERS:

Connection #1	Female	F-VEP13P ½ BSP-A10
Connection #2	Male	M-VEP13P ½ BSP-A10
Working pressure	[bar]	200